

PANEL THICKNESS	WALL PANEL SPAN IN FEET (L/180)						
	5	8	10	12	14	16	18
2"	48	29	22	-	-	-	-
2.5"	51	30	24	19	-	-	-
3"	53	31	24	20	17	-	-
4"	57	34	26	21	18	16	-
5"	60	36	28	23	19	17	14
6"	60	36	28	23	19	17	15

**CONDITIONS:**

Panel Series: 900  
 Design Parameter: Uniform Load  
 Fastening Method: (3) Through Fasteners w/ washers  
 Exterior Face: 26 Ga. Galvanized Steel  
 Interior Face: 26 Ga. Galvanized Steel  
 Deflection Limit: L/180

**NOTES TO TABLE:**

- Spans shown are simple and limited by deflection under uniform load only. Spans may be governed by other factors including deflection due to temperature differentials, multiple spans, and negative wind pressure and connection points required for fasteners. Consult Kingspan for specific project applications.

PANEL THICKNESS	WEIGHT PER SQ. FT.		
	26 GA / 26 GA	24 GA / 26 GA	24 GA / 24 GA
2"	2.27	2.52	2.74
2.5"	2.38	2.62	2.84
3"	2.48	2.73	2.95
4"	2.69	2.94	3.16
5"	2.9	3.15	3.37
6"	3.11	3.35	3.57

